## ROLLER'S Uni-Press ACC



German Top Quality







Robust, compact electric radial press 32 kN with automatic return (forced return). For radial press joints Ø 10–108 (110) mm, Ø 3/4–4"

- Universal for all ROLLER'S pressing tongs (except ROLLER'S pressing tongs Mini) and ROLLER'S pressing rings, as well as for suitable pressing tongs / pressing rings of other makes.
- Compact design, perfect weight distribution for real one-hand operation, comfortable weight, drive unit only 4.7 kg.
- Tiltable pressing tongs (through 360°) by housing on rotary bearing.
- Pressing process in inching mode with ACC for work safety, functional safety and operating safety. Automatic return (forced return) after completed pressing. Automatic return (forced return) after completed pressing.
- Several tons feed and pressing force for perfect, split-second pressing. Thrust 32 kN. Robust, powerful, electrohydraulic drive with eccenter piston pump with robust planetary gear and compact high-performance hydraulic system.
- Proven, powerful 1~ universal motor 230 V, 50−60 Hz, 450 W, with safety switch.
- Constant shear force for constantly reliable pressing.
- Secure seating of pressing tongs / adaptor tongs by automatic locking.
- Complete range of ROLLER'S pressing tongs / pressing rings for all common pressfitting systems, see page 100–140.

With precisely worked and exactly rounded, system-specific press contour according to the respective pressfitting system. For perfect system-conformant, reliable pressing.

The pressing tongs / pressing rings are made from tenacious, specially hardened special steel and they are therefore highly resistant. For maximum quality demands and long life.

ROLLER'S pressing tongs/pressing rings fit all ROLLER'S 32 kN radial presses and suitable drive units of other makes with 32 kN thrust.

All pressing tongs marked by a \* have an additional connection for manual driving by the ROLLER'S Easy-Press drive unit.

All pressing rings S (PR-2B) marked with \*\* can also be driven with the manual radial press ROLLER'S Easy-Press using the adapter tong Z8, see page 140.

- Confirmations of suitability see page 52.
- Liability acceptance agreements see page 53.

Scope of Delivery Art.-No. €

## ROLLER'S Uni-Press ACC Basic-Pack

32 kN drive unit with forced return.

 Basic-Pack in steel case
 577010 A220
 1.462,54

 Basic-Pack in L-Boxx system case
 577013 A220
 1.504,06

Accessories

See page 100-140	
8,74	
0,03	
6,36	
,	

