
ROLLER'S Worklight 10000





Powerful, handy, mobile LED flood light for universal use. With 2 brightness stages with 5000 lm and 10000 lm light flux.

- With high light intensity for universal use on the construction site and in the workshop.
- Handy, light, only 3.0 kg.
- Impact-resistant aluminium housing, dust-proof, protected against water jets from all directions. With 360° rotation for optimum alignment, fastenable without tools by wing nuts. LEDs protected by impact-resistant, unbreakable acrylic glass.
- Tubular steel frame with rubber feet for firm stand. Practical, non-slip handle.
 On/Off switch.
- Modern, energy-saving LED area flood light with high light intensity. Brightness
 of the LEDs adjustable in 2 stages. Radiation angle of 120° for high illumination.
 Colour temperature 5,000 K. Power 100 W. Overheating protection controls the
 power supply automatically for continuous operation
- Practical, collapsible, telescopic tripod stand, for exact positioning of the LED flood light. Only 1.9 kg. Height-adjustable from 615 to 1590 mm from the floor (accessory).

Scope of Delivery	ArtNo.	€
ROLLER'S Worklight 10000		
Construction site flood light with aluminium housing, LED area flood light, 2 brightness stages, tubular steel frame with rubber feet	175222 A220	123,52
Accessories		
ROLLER'S telescopic stand 3B on tripod height-adjustable collapsible	175230 A	31 04