ROLLER'S Centro S1 / SR / S2/3.5 / DP



Accessory for DOLLED'S Contro S1 Contro SD		
Accessory for ROLLER'S Centro S1, Centro SR, Centro S3, Centro S2 / 3.5, Centro DP and other makes	ArtNo.	Kč
Drilling template drill stand T	192605 D	1 670 00
for easy setting of the fastening holes Laser drilling centre pointer	183605 R 183604 R	1 670,00 3 750,00
Carbide masonry drills Ø 15 mm SDS-plus	103004 K	3750,00
for hammer anchors M12	079018	814,00
Hammer anchor M12 (concrete), 50 pieces	079005 R50	3 180,00
Setting iron for hammer anchor M 12	182050 R	466,00
Carbide masonry drills Ø 20 mm SDS-plus for splaying anchors M12	079019	1 840,00
Splaying anchor M12 , pack of 10, for masonry, reusable	079006 R10	2970,00
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.	079010	2 110,00
Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm,		
2 quick clamping nuts, 2 washers	183607 R	1 570,00
Vacuum fastening drill stand T, consisting of sealing ring and cover plate with hose connection	183603 R	2 880,00
Vacuum pump , for vacuum \leq - 900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m3/h, condenser motor 230 V, 50–60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with		
bayonet coupling	183670 R220	55 200,00
Start drilling aid G ½ UDKB, with holes for extracting the drilling dust from the bore hole by a suction rotor for dust extraction (Art. No. 181160 R), with carbide masonry drill Ø 8 mm	180140 R	2660,00
Start drilling aid G ½ TDKB, with holes for extracting the drilling dust from the bore hole, with carbide		,
masonry drill Ø 8 mm	180145 R	2 660,00
Carbide masonry drill Ø 8 mm for drill aid	079013	546,00
Pressurised water tank for 10 l of water, for wet drilling without water connection	182006 A	5940,00
Water extractor for wet drilling up to Ø 170 mm, consisting of water collection ring with sealing ring, rubber washer Ø 200 mm and universal pressure pad for all		
ROLLER'S drilling stands. Rubber disc, Ø 200 mm, pack of 10,	183606 R	11 370,00
for water extractor	183675 R10	2 160,00
Suction rotor for sucking off dust with G ½ male thread, UNC 1¼ male thread and with connection for ROLLER'S Protector 2		
and other suitable extractors	180160 R	5020,00
Levelling block magnetic, for aligning the drill stand	182010 A	2 180,00
Drilling crown extension 200 mm	180155 R	1 770,00
Easy loosening ring for easy loosening of the diamond core drilling crown	180015	598,00
Sharpening stone for diamond core drilling crowns	079012	1 870,00
Single open ended wrench SW 41 for loosening of the drilling crown	079003	1 110,00
ROLLER'S Protector 2 L / M Dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts		
in accordance with EN 60335-2-69	See page 207	