ROLLER'S Corso St





Robust, quality pipe cutter for steel pipes Ø $\frac{1}{8}$ -4", Ø 10-115 mm, wall thickness s \leq 12.5 mm.

- Robust, solid bow of forged steel.
- Strong spindle, long spindle guide and hardened guide rollers, for exact guiding on the pipe and long life.
- Wide, ergonomic handle enables powerful engagement of the spindle.
- Precision, wide cutting wheel bearing on hardened, twist-protected axle ensures right-angled cutting.
- Proven quality cutting wheel made of tenacious special steel for extremely long life.
- Cutting wheel protected against touching the guide rollers by in-feed limitation.

Designation	Pipes Ø	ArtNo.	€
ROLLER'S Corso	St		
St 1/8-2"	1/ 01/ / 10 00	440000 4	244.00
with cutting wheel s 8	½−2" / 10−60 mm	113000 A	241,00
St 11/4-4" with cutting wheel s 8	1½-4"/30-115 mm	113100 A	440.00
s = wall thickness in mm			.,
Accessories			
Accessories			
Accessories ROLLER'S cutting whee	for ROLLER'S	341614 A	16,40
Accessories ROLLER'S cutting whee (wall thickness s ≤ 8 mm)	for ROLLER'S S Corso St 1½–4" I St 1–4", s 12	341614 A	16,40

ROLLER'S Corso Cu/INOX S





With quick adjustment

German Top Quality

Compact, robust quality pipe cutter with cutting wheel and counter pressure rollers on needle bearings for thin-walled, stainless steel pipes, copper pipes and others, Ø 3–64 mm, Ø $\frac{1}{2}$, wall thickness s \leq 4 mm.

- Mounted on needle bearing, very smooth action, for effortless, fast cutting.
- Ideal for stainless steel pipes.
- Proven quality cutting wheel made from tenacious special steel for extremely long life. Only one cutting wheel for the entire working range Ø 3 – 64 mm, to fit all ROLLER'S Corso Cu/NOX S pipe cutters. Quick cutting wheel change without tools (Corso Cu/INOX 3-28 S Mini and 3-35 S).
- Cutting wheel protected against touching the guide rollers by in-feed limitation
- <u>ROLLER'S Corso Cu/INOX 3-28 S Mini</u>
 Small, handy, easy grip design, especially for places with difficult access.
- ROLLER'S Corso Cu/INOX 3-35 S
 With space-saving, special smooth action telescopic spindle for fast, easy engagement and simple, right-angled cutting. Integrated pipe deburrer with specially ground, exchangeable deburring blade. 4 hardened counter pressure rollers, for exact guiding on the pipe and long life.
- ROLLER'S Corso Cu/INOX 8-64 S
 Fast positioning of the cutting wheel in both directions. No unnecessary forward and backward turning of the spindle. For fast working. Strong spindle, long spindle guide and hardened guide rollers, for exact guiding on the pipe and long life.

Designation	Pipes Ø	ArtNo.	€
ROLLER'S Corso C	u/INOX S		
Cu/INOX 3-28 S Mini	3-28 mm / 1/8-11/8"	113241 A	59,10
Cu/INOX 3-35 S	3-35 mm / 1/8-1 3/8"	113351 A	86,90
Cu/INOX 8-64 S	8-64 mm / 3/8-21/2"	113401 A	219,00
Accessories			
ROLLER'S cutting wheel needle bearing, wall thickne	•	113213 A	22,40
Universal deburring blade	e		
specially ground			