

ROLLER'S dry-diamond core drilling crowns LS





High temperature-resistant dry diamond core drilling crowns, laser-welded. Especially for dry drilling with core drilling machines with micro-pulse technology, hand held or with drill stand. For many materials, e.g. concrete, steel-reinforced concrete, all kinds of masonry, natural stone, asphalt, all kinds of screed. Connection thread UNC 11/4 female, drilling depth 320 mm.

- Driven by ROLLER'S Centro DP with micro-pulse technology and by suitable drive • units of other makes with UNC 11/4 male connection thread.
- Diamond segments with diamonds positioned in the bonding agent. For fast, easy and smooth drilling.
- Laser-welded on fully automatic welding machines for consistent high quality of the weld. High temperature-resistant, even under extreme temperature load, no desoldering of the segments due to overheating.
- High quality diamond segments with special bonding with high diamond content for fast drilling and very long life. Universal for use in steel-reinforced concrete, granite, lime sandstone, sandstone, Poroton, brick, asphalt.
- Use ROLLER'S Protector 2 M for high-performance extraction of the drilling dusts from the drilling gap during dry drilling, see page 207. ROLLER'S Protector 2 M dry and wet extractor is certified for the extraction of health hazardous dusts of dust class M.
- Easy loosening ring, for easy loosening of the drilling crown (accessory). •

Designation Ø × drilling depth × connection	Number of segment	ArtNo. ts	€
ROLLER'S dry-diamond co	re drilling ci	rowns LS	
TDKB LS 32 × 320 × UNC 1¼	3	181500 A	183,00
TDKB LS 42 × 320 × UNC 1¼	4	181502 A	171,00
TDKB LS 52 × 320 × UNC 1¼	5	181504 A	182,00
TDKB LS 62 × 320 × UNC 1¼	5	181506 A	198,00
TDKB LS 72 × 320 × UNC 1¼	6	181508 A	225,00
TDKB LS 82 × 320 × UNC 1¼	6	181510 A	244,00
TDKB LS 92 × 320 × UNC 1¼	6	181512 A	274,00
TDKB LS 102 × 320 × UNC 1¼	7	181514 A	281,00
TDKB LS 112 × 320 × UNC 1¼	7	181516 A	296,00
TDKB LS 122 × 320 × UNC 1¼	8	181532 A	340,00
TDKB LS 127 × 320 × UNC 1¼	8	181518 A	353,00
TDKB LS 132 × 320 × UNC 1¼	8	181520 A	362,00
TDKB LS 142 × 320 × UNC 1¼	8	181522 A	388,00
TDKB LS 152 × 320 × UNC 1¼	8	181524 A	432,00
TDKB LS 162 × 320 × UNC 1¼	9	181526 A	458,00
TDKB LS 182 × 320 × UNC 1¼	9	181528 A	510,00
TDKB LS 202 × 320 × UNC 1¼	10	181530 A	540,00
Accessories			
Drilling crown extension 200 mm		180155 R	64,90
Easy loosening ring for easy loosening of the diamond core drilling crown		180015	21,90
Sharpening stone for diamond core drilling crowns		079012	68,60
Single open ended wrench SW 41			





-		,
8	181522 A	388,00
8	181524 A	432,00
9	181526 A	458,00
9	181528 A	510,00
10	181530 A	540,00
Drilling crown extension 200 mm		64,90
ing		
of the diamond core drilling crown Sharpening stone for diamond core drilling crowns		21,90
		68,60
for loosening of the drilling crown		40,70
	8 9 9 10	8 181524 A 9 181526 A 9 181528 A 10 181530 A 180155 R 180015



