

## ROLLER'S *Assistant*



German Top Quality

**Robust, continuously height adjustable material rest with ball guide for pipes  $\varnothing$  ( $\frac{1}{8}$ )  $\frac{3}{4}$ –6",  $\varnothing$  (6) 26–115 mm, solid material  $\varnothing$  (6) 26–150 mm, load capacity up to 150 kg.**

- Ideal for pipe installation, e.g. when cutting, thread cutting, sawing, welding and soldering.
- Stainless steel ball guide, suitable for rotating and standing pipe and solid material. Easy movement of the material in all directions.
- **ROLLER'S Assistant 3B**  
On sturdy, firm tripod. Collapsible for transport and storage. Height-adjustable from 690 to 1180 mm from the floor.
- **ROLLER'S Assistant WB**  
With clamping device for workbench. Height-adjustable from 35 to 580 mm from the workbench surface.

| Scope of Delivery  | Art.-No. | €             |
|--|----------|---------------|
| <b>ROLLER'S Assistant 3B</b><br>on tripod                          | 120120 A | <b>387,00</b> |
| <b>ROLLER'S Assistant WB</b><br>With clamping device for workbench | 120130 A | <b>233,00</b> |

## ROLLER'S *Assistant XL 12"*



**Ultra-strong, continuously height-adjustable material rest with ball guide for pipes, solid material  $\varnothing$  ( $\frac{1}{8}$ ) 1 $\frac{1}{4}$ –12",  $\varnothing$  (6) 42–324 mm, load capacity up to 450 kg.**

- Ideal for pipe installation, e.g. when roller grooving, cutting, thread cutting, sawing, welding and soldering.
- Stainless steel ball guide, suitable for rotating and standing pipe and solid material. Easy movement of the material in all directions.
- Robust structure suitable for building sites. Safe standing tripod, collapsible for transport and storage.
- Height-adjustable from 505 to 915 mm from the floor.
- Threaded spindle for easy alignment of the pipe, with fixing device.
- Practical handle for easy transport.

| Scope of Delivery  | Art.-No. | €             |
|--|----------|---------------|
| <b>ROLLER'S Assistant XL 12"</b><br>on tripod, collapsible | 120125 A | <b>419,00</b> |