

ROLLER'S

Axial-Press 25 / 25 L 22V ACC



←ACC→
Automatic Circuit Control
with automatic return and
battery charging status check

German Top Quality



Axial-Press 25

For systems:
e.g. aquatherm,
General Fittings,
IVT,
REHAU,
REVEL,
Seppelfricke,
TECE,
TIEMME,
Würth



Axial-Press 25 L

For systems:
e.g. AC-FIX,
BARBI,
Brass & Fittings,
EUROP FLUIDES,
FERRO systems
BRASELI,
Fittings Estándar,
PLÁSTICOS FERRO,
Velta



Ultra handy, ultra light, robust hybrid axial press 20 kN or 13 kN for cordless and mains operation, with automatic return (ACC). For compression sleeve connections Ø 12–40 mm. Li-Ion 22 V Technology! Li-Ion 21.6 V, 2.5 Ah battery for approx. 500 pressings per battery charge*.

- Only one universal drive unit for ROLLER'S compression heads according to the requirements of the respective compression sleeve system for fast, perfectly system-conformant, reliable pressing.
- Small, compact design with perfect weight distribution for real one-hand operation. Comfortable weight, drive unit with battery only 3.0 kg (ROLLER'S Axial-Press 25 22 V ACC) or only 3.2 kg (ROLLER'S Axial-Press 25 L 22 V ACC), for fatigue-free working.
- Extra handy drive unit, with press head only 28 cm (ROLLER'S Axial-Press 25 22 V ACC) or 31 cm (ROLLER'S Axial-Press 25 L 22 V ACC) long. For working in very confined spaces.
- **ROLLER'S Axial-Press 25** with preset compression head position for pressing compression sleeve connectors with a clamping distance up to a ≤ 82 mm in one action. Stroke length 40 mm.
- **ROLLER'S Axial-Press 25 L** with selectable compression head position for pressing compression sleeve connectors with a clamping distance up to a ≤ 116 mm in one action. Stroke length 40 mm.
- Automatic return (ACC) after successfully completed pressing.
- Rotating press device for working in very confined spaces.
- High pressing force for perfect, split-second pressing. ROLLER'S Axial-Press 25 22 V ACC 20 kN, thrust, ROLLER'S Axial-Press 25 L 22 V ACC 13 kN thrust. Robust, powerful, electro-hydraulic drive with eccentric piston pump with robust planetary gear and compact high-performance hydraulic system.
- Proven, powerful battery motor 21.6 V, 380 W output, safety switch.
- Integrated LED work light for illuminating the work place.
- Constant shear force for constantly reliable pressing.
- **Li-Ion 22 V technology**
Highly resistant Li-Ion 21.6 V batteries with 2.5, 5.0 or 9.0Ah capacity, for long service life. Powerful and light. Li-Ion 21.6 V, 2.5 Ah for approx. 500 pressings, 5.0 Ah for approx. 1,000 pressings, 9.0 Ah for approx. 1,800 pressings Rehau RAUTITAN PX Ø 16 mm per battery charge*. Graduated charging status indicator with coloured LEDs. Operating temperature range –10 to +60 °C. No memory effect for maximum battery power. 100–240 V, 50–60 Hz, 90 W rapid charger or 100–240 V, 50–60 Hz, 290 W rapid charger, for shorter charging times (accessories).
- **For cordless and mains operation**
220–240 V/21.6 V, 50–60 Hz, 15 A (output), power supply for mains operation instead of Li-Ion 21.6 V battery (accessory).
- **Full range of system-specific ROLLER'S compression heads**
for all common compression sleeve systems, according to the requirements of the respective compression sleeve system as well as ROLLER'S compression heads with spring catch for accommodating conventional pressing inserts, see page 144–145.
- **Double pressing heads**
ROLLER'S double pressing heads with two mountings that merge into each other, for pipe connectors of different dimensions, see page 144. No changing of pressing heads. Super fast and easy.
- Hybrid and manual pipe expander as well as full range of system-specific ROLLER'S expander heads P for all common compression sleeve systems, according to the requirements of the respective compression sleeve system, see page 146–149.
- Quickly and easily changeable compression heads and expander heads, without tools.

Scope of Delivery

Art.-No.

€

ROLLER'S Axial-Press 25 22V ACC Basic-Pack

21.6 V, 20 kN drive unit, with clamping distance
a ≤ 82 mm, Li-Ion 21.6 V, 2.5 Ah battery,
100–240 V, 70 W rapid charger, in steel case

573023 A220

1.670,00

ROLLER'S Axial-Press 25 22V L ACC Basic-Pack

21.6 V, 13 kN drive unit, with clamping distance
a ≤ 116 mm, Li-Ion 21.6 V, 2.5 Ah battery,
100–240 V, 70 W rapid charger, in steel case

573023 A220

1.670,00

Accessories

ROLLER'S compression heads	See page 144–145	
ROLLER'S Axial-Press 25 22V ACC drive unit, without battery	573020 A22	1.250,00
ROLLER'S Axial-Press 25 22V L ACC drive unit, without battery	573021 A22	1.250,00
Li-Ion 21.6 V batteries, 100–240 V rapid chargers, 220–240 V/21.6 V power supply	see page 147	
Steel case with inlay	578290 A	128,00
ROLLER'S Worklight 2800 22V cordless LED flood light	see page 173	