ROLLER'S Filou Cu/INOX



German Top Quality



Powerful, compact. robust pipe circular saw especially for stainless steel pipes, carbon steel pipes and copper pipes of the pressfitting systems, $\leq \emptyset$ 76 mm. Also for cutting thin-walled profiles for before-wall installation.

- Ideal for low-burr, right-angled and fast sawing of stainless steel tubes and copper tubes of the pressfitting systems, e. g. Ø 22 mm in only 4 s.
- Adapted to the requirements of the pressfitting systems: Dry sawing, therefore no damage to the O-ring by lubricants. Low-burr sawing by double vice.

Optimum cutting speed damage to the pipe material by overheating.

- Stable, smooth action universal double vice with only one clamping spindle for fast, easy clamping. Both material ends remain firmly clamped during sawing. Secure clamping also of thin-walled pipes by vertically inclined low tension jaw.
- Fast, easy and quiet sawing by favourable lever effect and ideal speed (60 rpm).
- Low weight, easily portable, only 17 kg. For workbench, subframe or mobile subframe (accessory).
- Robust, maintenance-free gear with high efficiency.
- Proven, powerful 1~ universal motor 230 V, 50–60 Hz, 500 W, with safety switch.
- Fine-toothed, hardened, specially ground ROLLER'S metal circular saw blades HSS or HSS-E (cobalt alloyed), 225 × 2 × 32 mm, 220 teeth (accessory) for easy, accurate sawing and long life.
- Connection for fitting the ROLLER'S Rondo 10–54 E pipe deburrer.

| Scope of Delivery | ArtNo. | € |
|--|--------------|----------|
| ROLLER'S Filou Cu/INOX | | |
| Saw with universal double vice, ring spanner, allen key, without saw blade | 849006 A220 | 1.430,00 |
| Accessories | | |
| ROLLER'S metal circular saw blade HSS 225×2×32mm, 220 teeth, especially for stainless steel pipe | 849703 A | 257.00 |
| ROLLER'S metal circular saw blades HSS-E (cobalt alloyed) 225 × 2 × 32 mm, 220 teeth, especially for stainless steel pipe, for very long life | 849706 A | 358,00 |
| ROLLER'S Rondo 10–54 E universal outer/inner pipe deburrer Ø 10–54 mm | See page 168 | |
| Subframe | 849315 R | 251,00 |
| Subframe, mobile | 849310 R | 407,00 |
| ROLLER'S Werkmeister, collapsible workbenches ROLLER'S Assistent, height adjustable | See page 170 | |
| material rests | See page 172 | |









ß

S