

# ROLLER'S

## Multi-Press XL 45 kN 22 V ACC



**←ACC→**  
Automatic Circuit Control  
with forced return and  
battery charging status check

German Top Quality



**Powerful, universal, robust hybrid radial press XL 45 kN for cordless and mains operation with automatic circuit control. Antivibration system. For radial press joints XL Ø 64–108 mm, Ø 2½–4". Li-Ion 22 V Technology! Li-Ion 21.6 V, 5.0 Ah battery for approx. 150 pressings per battery charge\*.**

- For driving adaptor tongs Z7 XL 45 kN with ROLLER'S pressing rings XL (PR-3S).
- Long working stroke for pressings in just one action. Ultra-fast, e.g. Geberit Mapress Stainless-steel Ø 108 mm in only 15 s.
- Compact, slim, suitable for building sites. Drive unit with battery pack weighs only 6.5 kg.
- Ergonomically designed housing with soft grip.
- Rotating pressing ring seat (over 360°).
- Pressing process with ACC – for work safety and operating safety. Automatic return (forced return) after completed pressing.
- **Anti-vibration system**  
Special drive technology with weight compensation and soft grip handles, for low-vibration, fatigue-free pressing.
- Several tons feed and pressing force for perfect, split-second pressing. Thrust 45 kN. Robust, powerful, electrohydraulic drive with eccentric dual-piston pump with robust planetary gear and compact high-performance hydraulic system. Constant shear force for constantly reliable pressing.
- Proven, powerful battery motor 21.6 V, 380 W output, safety switch. Machine status check.
- Integrated LED work light for illuminating the work place.
- **Li-Ion 22 V Technology**  
Highly resistant Li-Ion 21.6 V batteries with 5.0 or 9.0 Ah capacity, for long service life. Powerful and light. Li-Ion 21.6 V, 5.0 Ah battery for approx. 150 pressings, 9.0 Ah for approx. 270 pressings Geberit Mapress Stainless-steel Ø 108.0 mm per battery charge\*. Graduated charging status indicator by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. 100–240 V, 50–60 Hz, 90 W rapid charger or 100–240 V, 50–60 Hz, 290 W rapid charger, for shorter charging times (accessories).
- **For cordless and mains operation**  
220–240 V/21.6 V, 50–60 Hz, 40 A (output), power supply for mains operation instead of Li-Ion 21.6 V battery (accessory).
- Secure seating of the adaptor tongs by automatic locking.
- **Complete range of ROLLER'S XL pressing rings** for all common pressfitting systems, see page 100–140.  
With precisely worked and exactly rounded, system-specific press contour according to the respective pressfitting system. For perfect system-conformant, reliable pressing.  
The pressing tongs / pressing rings are made from tenacious, specially hardened special steel and they are therefore highly resistant. For maximum quality demands and long life.
- Confirmations of suitability see page 52.
- Liability acceptance agreements see page 53.

Scope of Delivery Art.-No. €

### ROLLER'S Multi-Press XL 45 kN 22 V ACC Basic-Pack Z7

21.6 V, 45 kN drive unit forced return and pressure monitoring, Li-Ion 21.6 V, 5.0 Ah battery, 100–240 V, 90 W rapid charger, adapter tongs Z7 XL 45 kN. In XL-Boxx system case.

579014 A220 **3.530,00**

#### Accessories

Accessories	Art.-No.	Price
<b>ROLLER'S pressing rings XL</b>	See page 100–140	
<b>Z7 XL 45 kN adapter tongs for driving the ROLLER'S pressing rings 64.0 – 108.0 XL (PR-3S), 2½–4" XL (PR-3S), 2½–4" XL (PR-3B) with ROLLER'S Multi-Press XL 45 kN 22 V ACC</b>	579123 R	456,00
<b>ROLLER'S Multi-Press XL 45 kN 22 V ACC drive unit, without battery</b>	579001 A22	2.390,00
<b>Li-Ion 21.6 V, 5.0 Ah battery</b>	571581 A22	359,00
<b>Li-Ion 21.6 V, 9.0 Ah battery</b>	571583 A22	479,00
<b>100–240 V, 50–60 Hz, 90 W rapid charger</b>	571585 A220	203,00
<b>100–240 V, 50–60 Hz, 290 W rapid charger</b>	571587 A220	479,00
<b>220–240 V/21.6 V, 50–60 Hz, 40 A power supply, for mains operation instead of Li-Ion 21.6 V battery</b>	571578 A220	600,00
<b>XL-Boxx system case with inlay</b>	579601 A	287,00
<b>ROLLER'S Worklight 2800 22 V cordless LED flood light</b>	see page 173	