ROLLER'S Polar



Universal pipe freezer for repairs on unemptied pipes with carbon dioxide coolant, for pipes Ø $\frac{1}{6}$ -2", 10-60 mm.

- No emptying, no filling, no venting. Saves time and money.
- Coolant carbon dioxide: Fast freezing time (e.g. ¾" in only 5 min) by up to -79° • cooling performance. Non-flammable, non-toxic, universally available.
- Very narrow, indestructible freezing sleeves.
- Snug-fit freezing sleeves and feeding of the coolant directly to the pipe guarantee • extremely short freezing times and economical use of coolant.
- Ergonomically designed plastic handles.
- Indestructible injector (injection nozzle) made of brass. Fast, secure connection to freezing sleeves. No setting, the right quantity of coolant is always dosed automatically.

Scope of Delivery	ArtNo.	€
ROLLER'S Polar Set		

2 pieces each freezing sleeves in 10 different sizes, Ø 10–60 mm. $\frac{1}{9}$ –2", bottle connection with T-adapt

Ø 10–60 mm, $\frac{1}{2}$ –2", bottle connection with T-adaptor,	
1 lock nut. 2 handle pieces with iniector.	

r lock hul, z handle pieces with injector,		
2 pieces high-pressure hoses 2 m, in case	130002 A	630,00

accoriac

Accessories				
Freezing sleeve	1/8"	10/12 mm	130450	46,70
	1⁄4"	15 mm	130455	46,70
	3/8	18 mm	130460	46,70
	1/2"	22 mm	130465	46,70
	3/4"	28 mm	130470	46,70
	1"	35 mm	130475	46,70
	11⁄4"	42 mm	130480	62,20
	11/2"		130485	62,20
		54 mm	130490	62,20
	2"	60 mm	130495	62,20
High-pressure hose 2 m			130415	134,00
T-distributor for other sleep	ves		130207	29,40
Bottle connection with T-j	unction		130383	54,50
Locking nut			130209	7,20
Double nipple			130208	11,20
Handle with injector			130410	64,10
Case with inlay			130430 A	118,00





	/2	22 111111	130405	
	3⁄4"	28 mm	130470	
	1"	35 mm	130475	
	11/4"	42 mm	130480	
	11/2"		130485	
		54 mm	130490	
	2"	60 mm	130495	
High-pressure hose 2 m			130415	
T-distributor for other sleeves			130207	
Bottle connection with T-junction			130383	
Locking nut			130209	
Double nipple			130208	
Handle with injector			130410	
Case with inlay			130430 A	