ROLLER'S Smart-Cut 12V



German Top Quality







Handy, ultra light, robust cordless pipe cutter for pipes of the pressfitting systems of stainless steel, C-steel Ø 12–28 mm, copper Ø 10–35 mm, composite tubes Ø 10–40 mm

- For right-angled and fast cutting of pipes of the pressfitting systems, e.g. copper tube Ø 22 mm in only 3 s.
- Adapted to the requirements of the pressfitting systems: For cutting without external burr, by ROLLER'S special cutting wheel. For dry cutting, therefore no damage to the O-ring by lubricants. For fast cutting, without impairment of the pipe material by overheating. For chipless cutting, therefore no chips in the pipe system.
- For right-angle cutting, according to requirements.
- Ultra handy, mobile, ultra light, drive unit with battery only 2.1 kg.
- Easy to operate, no setting work necessary.
- Strong, distortion-free aluminium structure for right angled cutting.
- 3 sturdy, specially arranged counter-pressure rollers made of hardened precision steel for low-friction turning and safe guidance of the pipes to be cut in the whole working range Ø 10–40 mm and for optimisation of the contact points of the cutting wheel on the pipe to be cut (Patent EP 2 077 175). No setting work.
- Energy-saving working due to ergonomically designed pressing lever.
- Optimally set cutting speed (130 rpm) for fast, quiet cutting.
- Robust, maintenance-free gear, precision ball and needle bearing, for long life.
- Proven, powerful battery motor 12 V, 270 W output, with safety switch.
- Electronic charging status check with low discharge protection.
- Li-lon Technology:
- Li-Ion 12 V battery with 2.5 Ah capacity. Powerful and light. High energy density for many cuts. Overheating and overloading protection by temperature monitor (NTC). 220–240 V, 50–60 Hz, 10.8–18 V, 65 W rapid charger, for short charging times. No memory effect for maximum battery performance.
- Also for fixing to the workbench or in the vice.
- Cutting wheels with respective different cutting geometry are adapted to the performance data of ROLLER'S Smart-Cut 12 V and to the materials to be cut and ensure fast cutting without external burr. Cutting wheels made of proven, tenacious steel for extremely long life.

Scope of Delivery	ArtNo.	€
ROLLER'S Smart-Cut 12V Basic-Pack		
12 V drive unit with pipe rests, Li-Ion 12 V, 2.5 Ah, 220–240 V, 10.8–18 V, 65 W rapid charger, single open-ended wrench size 8, without cutting wheel, in carrying case	844011 A220	780,00
Accessories		
ROLLER'S cutting wheel Cu/INOX		
for pipes of the pressfitting systems of stainless steel, copper, C-steel	844050 A	44,20
ROLLER'S cutting wheel V		
for multilayer composite tubes	844051 A	44,20
Li-lon 12 V, 2.5 Ah battery	844510 A12	161,00
220–230 V, 50–60 Hz, 10.8–18 V, 65 W		
rapid charger	571560 A220	179,00
Carrying bag	574436 R	44,40
L-Boxx system case with inlay for ROLLER'S Smart-Cut/Smart-Cut 12 V rapid charger, battery,		
ROLLER'S Rondo 8–35, 2 ROLLER'S cutting wheels	844045 A	170,00
ROLLER'S Werkmeister, collapsible workbenches	See page 170	
ROLLER'S Assistent, height adjustable		
material rests	See page 172	

