

ROLLER'S King 1¼



Unique locking of the die head!

German Top Quality



Handy, compact, powerful electric thread cutting stock for pipe threads ½–1¼", 16–40 mm.

- For repairs, renovations and building sites.
- Compact design, favourable weight, drive unit only 4.5 kg for working without fatigue.
- Slim form, small dimensions, can therefore be used anywhere, in confined spaces, on ceilings, in trenches. Also without vice.
- Quick, easy changing of the die heads.
- Unique locking of the die head in the drive unit, therefore secure seat when starting to cut.
- Precision, robust ROLLER'S Central quick-change die heads with exactly fitting dies with optimum cutting geometry, for extremely easy cutting start and easy cutting of standard threads. Long, precision pipe guide for perfect centring of the pipe. Large chip window for perfect chip flow. Proven quality ROLLER'S Central dies made from special tenacious steel for extremely long life.
- Quick-change die heads also fit into the ROLLER'S Central manual die stock.
- Compact, robust, maintenance-free gear. Specially stepped for ideal force transmission.
- Proven, powerful 1~ universal motor 230 V, 50–60 Hz, 1,200 W, with 30 % power boost by automatic carbon brush adjustment in the direction or rotation selection, right and left-hand direction of rotation, thermal overload protection and safety switch.
- Very easy to handle, sturdy support bracket for supporting the torque in both directions. With self-reinforcing clamping effect by angled clamping spindle.
- ROLLER'S Nipparo, manually inside clamping nipple holder for rational production of nipples and double nipples in any desired length (accessory), see page 20.

Scope of Delivery

Art.-No.

€

ROLLER'S King 1¼ Set ½+¾+1+1¼

Drive unit, support bracket, quick-change die heads ROLLER'S Central R ½", ¾", 1", 1¼", for right-handed pipe thread ISO 7-1, EN 10226 (DIN 2999, BSPT), in steel case

847301 A220

1.162,56

ROLLER'S King 1¼ Set M 20+25+32+40 (M x 1.5)

Drive unit, support bracket, quick-change die heads ROLLER'S Central M 20, M 25, M 32, M 40 (M x 1.5) for threads EN 60423 on electric installation pipes, in steel case

847306 A220

1.302,69

Accessories

ROLLER'S King 1¼ drive unit

847309 A220

653,94

Support bracket ROLLER'S King 1¼

847310

165,04

Ratchet lever ROLLER'S Central ½–1¼" 16–40 mm

479092 A

158,81

Quick-change die heads ROLLER'S Central

See page 18

Dies ROLLER'S Central

See page 18

Dual purpose holder

for fixing to the workbench. For thread-cutting with ROLLER'S King 1¼ / ROLLER'S King 2 and for right-angled sawing with ROLLER'S Fox / Fox 22 V VE

543100

264,69

Steel case with inlay

847800 A

110,03

Thread cutting materials

See page 19

ROLLER'S Nipparo

manual inside clamping nipple holder

See page 20

ROLLER'S roll grooving device

See page 22

