

ROLLER'S Scirocco 50



High-performance, highly efficient, electric dehumidifier/building dryer for commercial use in trade and industry. Dehumidification capacity of ≤ 50 l/24 h, air volume ≤ 265 m³/h.

- For drying rooms quickly and effectively, e.g. after water damage and floods – for drying basements and other rooms and accelerated drying of concrete, masonry, plaster, screed, etc.
- Compact, handy design in sturdy plastic case. Weight 21 kg
- Large air intake surface area with washable air filters. Top air outlet for optimum air circulation.
- Condensation discharge into an internal 7.7 l condensation tank, hose can be fed out at the rear, for discharging condensation into a tank to be provided or directly into a drain pipe.
- **Electronic hygostat**
for controlling the desired air humidity: Automatic switching off when target humidity has been reached – automatic restarting with increasing humidity.
- **Cooling unit**
High dehumidification performance by the high-quality cooling unit with highly efficient rotary compressor and high-performance capacitor motor 230 V, 680 W, with electronic thawing, for continuous operation. Very quiet running, also suitable for occupied rooms. Dehumidification capacity of ≤ 50 l/24 h, air volume ≤ 265 m³/h. High quality refrigerant R-290.
- **Electronic control unit**
Large illuminated control panel, with clear display of actual and nominal humidity, operating state of the cooling unit, thawing function. Buttons for setting the desired humidity to between 30% and 90% in 5 % increments, as well as setting for continuous operation. Buttons for 2 fan speeds. Button for timer. Memory function saves the settings for automatic continuation of operation following a power failure.
- Automatic switching off by switch-off signal when using the internal 7.7 l condensation tank when the maximum condensation level is reached
- Sturdy plastic housing with running rollers for easy transport.
- Operating hours counter and power consumption meter, e.g. for reporting to claims adjusters/customers (accessory).
- Condensation tank with condensation pump for feeding the condensation out of the condensation tank to a higher container or into a wash basin (accessory).
- ROLLER'S Mistral electric construction ventilator for supporting ROLLER'S Scirocco 50 / 80 (accessory). For improved air exchange and for faster drying after floods and mains water damage, see page 214.

Scope of Delivery

Art.-No.

€

ROLLER'S Scirocco 50 set

Electric dehumidifier/building drier with internal 7.7 l condensation tank. In sturdy plastic case with running rollers

132011 A220

777,46

Accessories

Condensation tank with pump Scirocco 50

For feeding the condensation out of the condensation tank to a higher container or into a wash basin. Transport height ≤ 2 m

132129 A220

389,25

Operating hours counter and power consumption meter e.g. for reporting to claims adjusters/customers.

132132 A220

54,81

ROLLER'S Control W

electric moisture measuring device for measuring the moisture in building materials, e.g. concrete, masonry, plaster, wood. In a bag.

132115 A

233,55

ROLLER'S Mistral 1360 / 2050

electric construction ventilator

see page 214