

# ROLLER'S

## Multi-Press 14V ACC

Two connections for ROLLER'S manual radial press and ROLLER'S 32 kN radial presses



German Top Quality



**Robust, compact hybrid radial press 32 kN for cordless and mains operation, with automatic return (forced return). For radial press joints Ø 10–108 (110) mm, Ø ¼–4". Li-Ion 14.4 V, 5.0 Ah battery for approx. 450 pressings per battery charge\*.**

- Universal for all ROLLER'S pressing tongues (except ROLLER'S pressing tongues Mini) and ROLLER'S pressing rings, as well as for suitable pressing tongues / pressing rings of other makes.
- Compact design, perfect weight distribution for real one-hand operation, comfortable weight, drive unit with battery only 4.3 kg.
- Tiltable pressing tongues (through 360°) by housing on rotary bearing.
- Pressing process in inching mode with ACC – for work safety, functional safety and operating safety. Automatic return (forced return) after completed pressing.
- Several tons feed and pressing force for perfect, split-second pressing. Thrust 32 kN. Robust, powerful, electrohydraulic drive with eccentric piston pump with robust planetary gear and compact high-performance hydraulic system.
- Proven, powerful battery motor 14.4 V, 380 W output, safety switch.
- Integrated LED work light for illuminating the work place.
- Constant shear force for constantly reliable pressing.
- **Li-Ion PLUS technology**  
Highly resistant Li-Ion 14.4 V battery with 5.0 Ah capacity, for long service life. Powerful and light. Li-Ion 14.4 V, 5.0 Ah battery for approx. 450 pressings Viega Profipress DN 15 per battery charge\*. Total discharge and overload protection with single cell monitoring. Temperature monitoring during the charging process. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. 220–240 V, 50–60 Hz, 10.8–18 V, 65 W rapid charger, for short charging times.
- **For cordless and mains operation**  
220–240 V/14.4 V, 33 A (output), power supply for mains operation instead of Li-Ion 14.4 V battery (accessory).
- Secure seating of pressing tongues / adaptor tongues by automatic locking.
- **Complete range of ROLLER'S pressing tongues / pressing rings** for all common pressfitting systems, see page 100–140.  
With precisely worked and exactly rounded, system-specific press contour according to the respective pressfitting system. For perfect system-conformant, reliable pressing.  
The pressing tongues / pressing rings are made from tenacious, specially hardened special steel and they are therefore highly resistant. For maximum quality demands and long life.  
ROLLER'S pressing tongues/pressing rings fit all ROLLER'S 32 kN radial presses and suitable drive units of other makes with 32 kN thrust.  
All pressing tongues marked by a \* have an additional connection for manual driving by the ROLLER'S Easy-Press drive unit.  
All pressing rings S (PR-2B) marked with \*\* can also be driven with the manual radial press ROLLER'S Easy-Press using the adapter tong Z8, see page 140.
- Confirmations of suitability see page 52.
- Liability acceptance agreements see page 53.

Scope of Delivery Art.-No. €

### ROLLER'S Multi-Press 14V ACC Basic-Pack

14.4 V, 32 kN drive unit, with automatic circuit control, Li-Ion 14.4 V, 5.0 Ah battery, 220–240 V, 10.8–18 V, 65 W rapid charger.

<b>Basic-Pack</b> in steel case	571014 A220	<b>1 880,00</b>
<b>Basic-Pack</b> in L-Boxx system case	571019 A220	<b>1 920,00</b>

### Accessories

<b>ROLLER'S pressing tongues / pressing rings</b>	See page 100–140	
<b>Adaptor tongues for ROLLER'S pressing rings</b>	See page 140	
<b>ROLLER'S Multi-Press 14V ACC drive unit, without battery</b>	571004 A14	1 400,00
<b>Li-Ion 14.4 V, 5.0 Ah battery</b>	571555 A14	251,00
<b>220–230 V, 50–60 Hz, 10.8–18 V, 65 W rapid charger</b>	571560 A220	171,00
<b>Li-Ion 220–240 V/14.4 V, 50–60 Hz, 33 A power supply, for mains operation instead of Li-Ion 14.4 V battery</b>	571565 A220	388,00
<b>ROLLER'S cropping tongs M for threaded bars</b>	See page 142	
<b>ROLLER'S cable shears for electric cables</b>	See page 142	
<b>Steel case with inlay</b>	571290 A	122,00
<b>L-Boxx system case with inlay</b>	571283 A	161,00