

ROLLER'S Centro

S1 / SR / S2/3.5 / DP



Accessories for ROLLER'S Centro S1, Centro SR, Centro S3, Centro S2 / 3.5, Centro DP and other makes	Art.-No.	€
Drilling template drill stand T for easy setting of the fastening holes	183605 R	63,40
Laser drilling centre pointer	183604 R	143,00
Carbide masonry drills Ø 15 mm SDS-plus for hammer anchors M12	079018	31,00
Hammer anchor M12 (concrete), 50 pieces	079005 R50	121,00
Setting iron for hammer anchor M 12	182050 R	17,70
Carbide masonry drills Ø 20 mm SDS-plus for splaying anchors M12	079019	69,80
Splaying anchor M12, pack of 10, for masonry, reusable	079006 R10	114,00
Quick clamping set 160 for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 x 52 thread, quick clamping nut, washer.	079010	80,10
Quick clamping set 500 for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers	183607 R	59,50
Vacuum fastening drill stand T , consisting of sealing ring and cover plate with hose connection	183603 R	110,00
Vacuum pump , for vacuum ≤ - 900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m ³ /h, condenser motor 230 V, 50–60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling	183670 R220	2 110,00
Start drilling aid G ½ UDKB , with holes for extracting the drilling dust from the bore hole by a suction rotor for dust extraction (Art. No. 181160 R), with carbide masonry drill Ø 8 mm	180140 R	102,00
Start drilling aid G ½ TDKB , with holes for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm	180145 R	102,00
Carbide masonry drill Ø 8 mm for drill aid	079013	20,80
Pressurised water tank for 10 l of water, for wet drilling without water connection	182006 A	227,00
Water extractor for wet drilling up to Ø 170 mm, consisting of water collection ring with sealing ring, rubber washer Ø 200 mm and universal pressure pad for all ROLLER'S drilling stands.	183606 R	433,00
Rubber disc, Ø 200 mm , pack of 10, for water extractor	183675 R10	82,00
Suction rotor for sucking off dust with G ½ male thread, UNC 1¼ male thread and with connection for ROLLER'S Protector 2 and other suitable extractors	180160 R	191,00
Levelling block magnetic, for aligning the drill stand	182010 A	82,80
Drilling crown extension 200 mm	180155 R	67,40
Easy loosening ring for easy loosening of the diamond core drilling crown	180015	22,80
Sharpening stone for diamond core drilling crowns	079012	71,20
Single open ended wrench SW 41 for loosening of the drilling crown	079003	42,20
ROLLER'S Protector 2 L / M Dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69	See page 207	