## ROLLER'S Corso St



# Robust, quality pipe cutter for steel pipes Ø $\frac{1}{6}$ -4", Ø 10-115 mm, wall thickness s ≤ 12.5 mm.

- Robust, solid bow of forged steel.
- Strong spindle, long spindle guide and hardened guide rollers, for exact guiding on the pipe and long life.
- Wide, ergonomic handle enables powerful engagement of the spindle.
- Precision, wide cutting wheel bearing on hardened, twist-protected axle ensures right-angled cutting.
- Proven quality cutting wheel made of tenacious special steel for extremely long life.
- Cutting wheel protected against touching the guide rollers by in-feed limitation.

Designation	Pipes Ø	ArtNo.	kr
ROLLER'S Corso S	t		
St <sup>1</sup> / <sub>8</sub> -2" with cutting wheel s 8	½–2" / 10–60 mm	113000 A	2 810,00
<b>St 11⁄4–4"</b> with cutting wheel s 8 s = wall thickness in mm	1¼–4" / 30– 115 mm	113100 A	5 120,00
Accessories			
<b>ROLLER'S cutting wheel</b> (wall thickness $s \le 8$ mm) f Corso St $\frac{1}{2}$ -2", ROLLER'S	or ROLLER'S	341614 A	200,00
<b>ROLLER'S cutting wheel</b> (wall thickness $s \le 12.5$ mr Corso St $1\frac{1}{4} - 4$ "		381622 A	440.00

### ROLLER'S Corso Cu/INOX S





With quick adjustment

<u>German Top Quality</u>

#### Compact, robust quality pipe cutter with cutting wheel and counter pressure rollers on needle bearings for thin-walled, stainless steel pipes, copper pipes and others, Ø 3–64 mm, Ø $\frac{1}{2} - 2\frac{1}{2}$ ", wall thickness s ≤ 4 mm.

- Mounted on needle bearing, very smooth action, for effortless, fast cutting.
- Ideal for stainless steel pipes.
- Proven quality cutting wheel made from tenacious special steel for extremely long life. Only one cutting wheel for the entire working range Ø 3 – 64 mm, to fit all ROLLER'S Corso Cu/NOX S pipe cutters. Quick cutting wheel change without tools (Corso Cu/INOX 3–28 S Mini and 3–35 S).
- Cutting wheel protected against touching the guide rollers by in-feed limitation
  <u>ROLLER'S Corso Cu/INOX 3–28 S Mini</u>
- Small, handy, easy grip design, especially for places with difficult access.
- <u>ROLLER'S Corso Cu/INOX 3–35 S</u> With space-saving, special smooth action telescopic spindle for fast, easy engagement and simple, right-angled cutting. Integrated pipe deburrer with specially ground, exchangeable deburring blade. 4 hardened counter pressure rollers, for exact guiding on the pipe and long life.
- <u>ROLLER'S Corso Cu/INOX 8–64 S</u> Fast positioning of the cutting wheel in both directions. No unnecessary forward and backward turning of the spindle. For fast working. Strong spindle, long spindle guide and hardened guide rollers, for exact guiding on the pipe and long life.

Designation	Pipes Ø	ArtNo.	kr
ROLLER'S Corso C	u/INOX S		
Cu/INOX 3–28 S Mini	3–28 mm / ½–1 ½"	113241 A	690,00
Cu/INOX 3-35 S	3–35 mm / ½–1¾"	113351 A	1 020,00
Cu/INOX 8–64 S	8–64 mm / ¾–2½"	113401 A	2 560,00
Accessories			
ROLLER'S cutting wheel needle bearing, wall thickne	· ·	113213 A	270,00
Universal deburring blade	9		
specially ground			

0

German Top Quality

### ROLLER'S Corso Cu/INOX









<u>German Top Quality</u>

With telescopic spindle



Small, handy pipe cutter for thin-walled, stainless steel tubes, copper tubes and others, Ø 3–28 mm, Ø  $\frac{1}{2}$ –1 $\frac{1}{2}$ ", wall thickness s  $\leq$  4 mm.

- Small, handy, easy grip design, especially for places with difficult access.
- Hardened guide rollers, for exact guiding on the pipe and long life.
- Proven quality cutting wheel made of tenacious special steel for extremely long life. Only one cutting wheel for all ROLLER'S Corso Cu/INOX pipe cutters. Quick cutting wheel change without tools.
- Cutting wheel protected against touching the guide rollers by in-feed limitation.

Designation	Pipes Ø	ArtNo.	kr
ROLLER'S Corso C	u/INOX		
Cu/INOX 3–16	3–16 mm / ½–%"	113200 A	360,00
Cu/INOX 3–25	3–25 mm / ⅓–1"	113230 A	430,00
Cu/INOX 3–28 Mini	3–28 mm / ½–1 ½"	113240 A	490,00
Accessories			
<b>ROLLER'S cutting wheel</b> (wall thickness s ≤ 4 mm) for all ROLLER'S Corso Co	,	113210 A	150,00

#### Compact, very robust quality pipe cutter for thin-walled, stainless steel tubes, copper tubes and others, Ø 3–120 mm, Ø $\frac{1}{4}$ –4", wall thickness s ≤ 4 mm.

- Handy, ergonomic rotary handle of metal enables powerful engagement of the spindle.
- Precision, wide cutting wheel bearing on hardened, twist-protected axle ensures right-angled cutting.
- Proven quality cutting wheel made of tenacious special steel for extremely long life. Only one cutting wheel for the entire working range Ø 3–120 mm, to fit all ROLLER'S Corso Cu/NOX pipe cutters. Quick cutting wheel change without tools (Corso Cu/INOX 3–28 and 3–35).
- Cutting wheel protected against touching the guide rollers by in-feed limitation.
- <u>ROLLER'S Corso Cu/INOX 3–35</u> With space-saving, special smooth action telescopic spindle for fast, easy engagement and simple, right-angled cutting. Integrated pipe deburrer with specially ground, exchangeable deburring blade. 4 hardened counter pressure rollers, for exact guiding on the pipe and long life.
- <u>ROLLER'S Corso Cu/INOX 3–28, 6–42, 6–64, 64–120</u> Strong spindle, long spindle guide and hardened guide rollers, for exact guiding on the pipe and long life.

Designation	Pipes Ø	ArtNo.	kr
ROLLER'S Corso C	u/INOX		
Cu/INOX 3-28	3–28 mm / ⅓–1 ⅛"	113300 A	420,00
Cu/INOX 3-35	3–35 mm / ½–1¾"	113350 A	760,00
Cu/INOX 6-42	6–42 mm / ¾–1¾"	113380 A	1 970,00
Cu/INOX 6-64	6–64 mm / ¼–2½"	113400 A	2 300,00
Cu/INOX 64-120	64–120 mm / 2½–4"	113500 A	3 330,00
Accessories			
<b>ROLLER'S cutting wheel</b> (wall thickness $s \le 4$ mm)	Cu / INOX 3–120, s 4		
for all ROLLER'S Corso Cu/INOX		113210 A	150,00
Universal deburring blade specially ground		113360	98,00