ROLLER'S Disc 100 ROLLER'S Disc 100 RF



German Top Quality





Compact, lightweight, robust pipe cutting machine for cutting and removing burr from pipes of the pressfitting systems of stainless steel, copper, C-steel, Ø 8–108 mm, steel pipes EN 10255 (DIN 2440) DN 6–100, Ø $\frac{1}{6}$ –4", Ø 10–115 mm, cast iron pipes (SML) EN 877 (DIN 19522) DN 50–100, plastic pipes SDR 11 wall thickness s ≤ 10 mm, Ø 10–110 mm, Ø $\frac{1}{4}$ –4", composite tubes Ø 10–110 mm. ROLLER'S Disc 100 RF for welded drain pipe/down pipe made of stainless steel EN 1124 Ø 40–110 mm

- Universal for cutting many types of pipes.
- Also ideal for right-angled and fast cutting of stainless steel tubes and copper
- tubes of the pressfitting systems, e. g. stainless steel tubes Ø 54 mm in only 4 s.
 Adapted to the requirements of the pressfitting systems:
 - For cutting without external burr, by ROLLER'S special cutting wheel. For dry cutting, therefore no damage to the O-ring by coolant-lubricants.
 - For fast cutting, without impairment of the pipe material by overheating.
 - For chipless cutting, therefore no chips in the pipe system.
 - For right-angle cutting, according to requirements.
- Easy to operate, no setting work, no tools necessary.
- Strong, torsion-free cast structure for right angled cutting. Easy cutting of the pipes by specially designed cutter wheel. Driven cutting wheel and straight feed for fast cutting (Patent EP 10 1 782 904). Effortless feeding by easy-grip, proven feed lever and trapezoidal screw spindle on needle bearing. Cutting wheel protected against touching the running rollers by in-feed limitation.
- ROLLER'S Disc 100
- with 4 strong, hardened precision tubular steel running rollers on ball bearings mounted for low-friction rotation of the pipes Ø 22–115 mm, Ø $\frac{3}{4}$ 4", to be cut, trapezoidally arranged, replaceable. No setting work in the whole working range Ø 22–115 mm. Stainless tubular steel rollers (accessory). Cutting of pipes
- Ø 8–22 mm by placing two pipe sections Ø 28 × 220 mm on the running rollers. ROLLER'S Disc 100 RF
- with 4 stable, polyamide running rollers on ball bearings, for avoiding damage to the pipe surfaces, for low-friction rotation of the welded drain pipes/downpipes to be cut made from stainless steel (EN 1124) Ø 40 – 110 mm; pipe guides Ø 75 and 110 mm prevent the pipe from becoming oval.
- Optimally set cutting speed (115 rpm) for fast, quiet cutting.
- Low weight, easily portable, only 16.8 kg.
- Robust, maintenance-free gear with high efficiency.
- Proven, powerful 1~ universal motor 230 V, 50–60 Hz, 1200 W, with safety foot switch.
- For workbench. Subframe or mobile subframe (accessory), for easy transport, optimum working height and stable positioning. An alternative feed lever is available for operating the drive unit on the floor (accessory).
- An alternative feed lever (accessory) is available for operating the drive unit on the floor. Pipe rest, height adjustable, for pipes Ø 40–110 mm, Ø 1½–4", for operation of the drive unit with feed lever on the floor (accessory).
- For fast easy removal of burr.
 For electrical drive by ROLLER'S Disc 100, ROLLER'S Disc 100 22 V pipe cutting machine

Inner pipe deburrer ROLLER'S Rondo 28–108

(accessory) for pipes Ø 28–108 mm, Ø 3/4–4". With surrounding friction element on the deburrer housing (**Patent EP 2 500 122**) for electric rotary drive by the cutting wheel of the pipe cutting machine ROLLER'S Disc 100, ROLLER'S Disc 100 22 V.


Inner/outer pipe deburrer ROLLER'S Rondo 10-54 E(accessory) for pipes Ø 10-54 mm, Ø $\frac{1}{2}-2$ %", see page 168.

Marking device for marking the insertion depth for fittings on pipes (accessory)

ROLLER'S Disc 100 ROLLER'S Disc 100 RF







Scope of Delivery	ArtNo.	kr
ROLLER'S Disc 100 Basic		
Drive unit with running rollers of hardened precision tubular steel, safety foot switch, ring spanner, without cutting wheel.	845001 A220	18 090,00
ROLLER'S Disc 100 RF Set		
Drive unit with polyamide running rollers, Ø 75 and 110 mm pipe guides, safety foot switch, ring spanner, with cutting wheel RF	845003 A220	28 720,00
Accessories		
ROLLER'S cutting wheel Cu/INOX for pipes of the pressfitting systems of stainless steel, copper, C-steel	845050 A	1 380,00
ROLLER'S cutting wheel Cu specially for pipes of the pressfitting systems of copper	845053 A	1 380,00
ROLLER'S cutting wheel St for steel pipes, cast pipes (SML)	845052 A	1 380,00
ROLLER'S cutting wheel V, s 10 for plastic and composite tubes (wall thickness $s \le 10$ mm)	845051 A	1 380,00
ROLLER'S cutting wheel C-SF especially for pipes of the pressfitting systems/push fitting systems of carbon steel, simultaneously produces a chamfer.	845055 A	1 380,00
ROLLER'S cutting wheel RF for welded drain pipe / down pipe made of stainless steel EN 1124 with ROLLER'S Disc 100 RF	845054 A	1 380,00
Feed lever with spring plug for operating the drive unit on the floor (for Disc 100 manufactured from 2014 onwards).	845218 R	1 140,00
Pipe rest 1 , height adjustable, for pipes \emptyset 40–110 mm, \emptyset 1½–4", with operation of the drive unit with feed lever on the floor	845220 R	1 890,00
Rollers, pack of 4, of hardened, precision steel	845118 R	2 660,00
Rollers INOX, pack of 4, of stainless steel	845110 RINOX	3 750,00
Rollers polyamide, pack of 4	845131 RPA	4 390,00
<i>Marking device</i> for marking the insertion depth for fittings on pipes. For ROLLER'S Disc 100 or Disc 100 22 V	845530 R	1 610,00
ROLLER'S Rondo 28–108 Inner pipe deburrers for pipes Ø 28–108 mm, Ø ¾–4". For electric rotary drive by the cutting wheel of the ROLLER'S Disc 100 or ROLLER'S Disc 100 22 V (with cutting wheel Art. No. 845050		
or 845053)	113840 A	4 1 20,00
ROLLER'S Rondo 10–54 E Inner/outer pipe deburrers for pipes Ø 10–54 mm	See page 168	
Subframe	849315 R	2 690,00
Subframe, mobile	849310 R	4 350,00
ROLLER'S Werkmeister, collapsible workbenches	See page 170	
ROLLER'S Assistent, height adjustable material rests	See page 172	
L-Boxx H system case for ROLLER'S Disc 100 / Disc 100 RF	845085 A	1 770,00