

ROLLER'S

Multi-Press XL 45 kN 22 V ACC



←ACC→
Automatic Circuit Control
with forced return and
battery charging status check

German Top Quality



Powerful, universal, robust hybrid radial press XL 45 kN for cordless and mains operation with automatic circuit control. Antivibration system. For radial press joints XL Ø 64–108 mm, Ø 2½–4". Li-Ion 22 V Technology! Li-Ion 21.6 V, 5.0 Ah battery for approx. 150 pressings per battery charge*.

- For driving adaptor tongs Z7 XL 45 kN with ROLLER'S pressing rings XL (PR-3S).
- Long working stroke for pressings in just one action. Ultra-fast, e.g. Geberit Mapress Stainless-steel Ø 108 mm in only 15 s.
- Compact, slim, suitable for building sites. Drive unit with battery pack weighs only 6.5 kg.
- Ergonomically designed housing with soft grip.
- Rotating pressing ring seat (over 360°).
- Pressing process with ACC – for work safety and operating safety. Automatic return (forced return) after completed pressing.
- **Anti-vibration system**
Special drive technology with weight compensation and soft grip handles, for low-vibration, fatigue-free pressing.
- Several tons feed and pressing force for perfect, split-second pressing. Thrust 45 kN. Robust, powerful, electrohydraulic drive with eccentric dual-piston pump with robust planetary gear and compact high-performance hydraulic system. Constant shear force for constantly reliable pressing.
- Proven, powerful battery motor 21.6 V, 380 W output, safety switch. Machine status check.
- Integrated LED work light for illuminating the work place.
- **Li-Ion 22 V Technology**
Highly resistant Li-Ion 21.6 V batteries with 5.0 or 9.0 Ah capacity, for long service life. Powerful and light. Li-Ion 21.6 V, 5.0 Ah battery for approx. 150 pressings, 9.0 Ah for approx. 270 pressings Geberit Mapress Stainless-steel Ø 108.0 mm per battery charge*. Graduated charging status indicator by coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. 100–240 V, 50–60 Hz, 90 W rapid charger or 100–240 V, 50–60 Hz, 290 W rapid charger, for shorter charging times (accessories).
- **For cordless and mains operation**
220–240 V/21.6 V, 50–60 Hz, 40 A (output), power supply for mains operation instead of Li-Ion 21.6 V battery (accessory).
- Secure seating of the adaptor tongs by automatic locking.
- **Complete range of ROLLER'S XL pressing rings** for all common pressfitting systems, see page 100–140.
With precisely worked and exactly rounded, system-specific press contour according to the respective pressfitting system. For perfect system-conformant, reliable pressing.
The pressing tongs / pressing rings are made from tenacious, specially hardened special steel and they are therefore highly resistant. For maximum quality demands and long life.
- Confirmations of suitability see page 52.
- Liability acceptance agreements see page 53.

Scope of Delivery Art.-No. kr

ROLLER'S Multi-Press XL 45 kN 22 V ACC Basic-Pack Z7

21.6 V, 45 kN drive unit forced return and pressure monitoring, Li-Ion 21.6 V, 5.0 Ah battery, 100–240 V, 90 W rapid charger, adapter tongs Z7 XL 45 kN. In XL-Boxx system case.

579014 A220 **39 470,00**

Accessories

Accessories	Art.-No.	kr
ROLLER'S pressing rings XL	See page 100–140	
Z7 XL 45 kN adapter tongs for driving the ROLLER'S pressing rings 64.0 – 108.0 XL (PR-3S), 2½–4" XL (PR-3S), 2½–4" XL (PR-3B) with ROLLER'S Multi-Press XL 45 kN 22 V ACC	579123 R	4 880,00
ROLLER'S Multi-Press XL 45 kN 22 V ACC drive unit, without battery	579001 A22	25 530,00
Li-Ion 21.6 V, 5.0 Ah battery	571581 A22	3 840,00
Li-Ion 21.6 V, 9.0 Ah battery	571583 A22	5 120,00
100–240 V, 50–60 Hz, 90 W rapid charger	571585 A220	2 170,00
100–240 V, 50–60 Hz, 290 W rapid charger	571587 A220	5 120,00
220–240 V/21.6 V, 50–60 Hz, 40 A power supply, for mains operation instead of Li-Ion 21.6 V battery	571578 A220	6 400,00
XL-Boxx system case with inlay	579601 A	3 070,00
ROLLER'S Worklight 2800 22 V cordless LED flood light	see page 173	