# ROLLER'S Pulsar





# Compact, powerful electric soft soldering device for copper tubes Ø 6-54 mm.

- Electric soldering without flame, no fire risk.
- Compact, handy, easy to transport.
- Large working radius by extra long soldering tongs cable (4 m).
- Universally applicable. With rod electrodes (accessory) also in confined spaces.
- Short soldering time by high heating power (900°C) and high soldering power (2000 W!).
- Immediately ready for soldering, no heating up time, no setting.
- Trouble-free working by temperature-independent control of the solder current with protective low voltage 24 V (safety transformer). No complicated setting of pneumatic controls.
- Easy changing of the electrodes. Stainless steel electrode holders and screws.

Scope of Delivery	ArtNo.	kr
ROLLER'S Pulsar		
Electric soft soldering device with soldering tongs, 4 m long soldering tongs cables, 2 prism electrodes	164011 A220	9 880,00
ROLLER'S Pulsar Super-Pack		
Electric soft soldering device with soldering tongs, 4 m long soldering tongs cables, 4 prism electrodes, 2 rod electrodes, ROLLER'S Corso Cu/INOX 3–35 pipe cutter, ROLLER'S Cloth cleaning cloth, in steel case	164050 A220	12 300,00
Accessories		
Prism electrode, pack of 2	164111 A	320,00
Prism electrode with holder, pack of 2	164110 A	530,00
Rod electrode, pack of 2	164115 A	330,00
Steel case with inlay	164250 A	1 600,00

160300 A

Art.-No.

130.00

kr

### **ROLLER'S Jet-Fire**

# Compact, robust propane blow torch for soft soldering of copper tubes up to Ø 35 mm.

- Self-igniting by piezo ignition, therefore lower gas consumption (only 200 g/h at full soldering power) and high work safety.
- Universal burner pipe with turbo-twist amplifier, flame temperature 1,950°C, for fast soft soldering.
- Handy, one-handed operation. No setting, no regulation.
- Locking knob for continuous operation.

#### ROLLER'S Jet-Fire

Scope of Delivery

ROLLER'S Vlies (pack of 10)

160010 A	3 020,00	
152106	1 120,00	
152109	1 440,00	
160300 A	130,00	
	152106 152109	



German Top Quality



S