ROLLER'S Scirocco 50











High-performance, highly efficient, electric dehumidifier/building dryer for commercial use in trade and industry. Dehumidification capacity of \leq 50 l/24 h, air volume \leq 265 m³/h.

- For drying rooms quickly and effectively, e.g. after water damage and floods for drying basements and other rooms and accelerated drying of concrete, masonry, plaster, screed, etc.
- Compact, handy design in sturdy plastic case. Weight 21 kg
- Large air intake surface area with washable air filters. Top air outlet for optimum air circulation.
- Condensation discharge into an internal 7.7 I condensation tank, hose can be fed
 out at the rear, for discharging condensation into a tank to be provided or directly
 into a drain pipe.
- Electronic hygrostat
- for controlling the desired air humidity: Automatic switching off when target humidity has been reached – automatic restarting with increasing humidity.
- Cooling unit

High dehumidification performance by the high-quality cooling unit with highly efficient rotary compressor and high-performance capacitor motor 230 V, 680 W, with electronic thawing, for continuous operation. Very quiet running, also suitable for occupied rooms. Dehumidification capacity of \leq 50 l/24 h, air volume \leq 265 m³/h. High quality refrigerant R-290.

• Electronic control unit

Large illuminated control panel, with clear display of actual and nominal humidity, operating state of the cooling unit, thawing function. Buttons for setting the desired humidity to between 30% and 90% in 5 % increments, as well as setting for continuous operation. Buttons for 2 fan speeds. Button for timer. Memory function saves the settings for automatic continuation of operation following a power failure.

- Automatic switching off by switch-off signal when using the internal 7.7 I
 condensation tank when the maximum condensation level is reached
- Sturdy plastic housing with running rollers for easy transport.
- Operating hours counter and power consumption meter, e.g. for reporting to claims adjusters/customers (accessory).
- Condensation tank with condensation pump for feeding the condensation out of the condensation tank to a higher container or into a wash basin (accessory).
- ROLLER'S Mistral electric construction ventilator for supporting ROLLER'S Scirocco 50 / 80 (accessory). For improved air exchange and for faster drying after floods and mains water damage, see page 214.

kr

Scope of Delivery	ArtNo.

ROLLER'S Scirocco 50 Set

Electric dehumidifier/building drier with internal 7.7 I condensation tank. In sturdy plastic case with running rollers	132011 A220	9 610,00
Accessories		
Condensation tank with pump Scirocco 50 For feeding the condensation out of the condensation tank to a higher container or into a wash basin. Transport height ≤ 2 m	132129 A220	4810,00
Operating hours counter and power consumption meter e.g. for reporting to claims adjusters/ customers.	132132 A220	680,00
ROLLER'S Control W electric moisture measuring device for measuring the moisture in building materials, e.g. concrete, masonry, plaster, wood. In a bag.	132115 A	2 890,00
ROLLER'S Mistral 1360 / 2050 electric construction ventilator	see page 214	

5

0

n o l