

ROLLER'S *Worklight 2800 22V*

Powerful, handy, mobile hybrid LED flood light, for cordless and mains operation, for universal use. With 3 brightness stages with 1100 lm, 2000 lm, 2800 lm light flux. Li-Ion 22V Technology.



- With high light intensity for universal use on the construction site and in the workshop.
- Handy, light, only 1.7 kg or with battery only 2.1 kg.
- Impact-resistant plastic housing, with 360° rotation for optimum alignment, fastenable without tools by wing nuts. LEDs protected by impact-resistant, unbreakable acrylic glass.
- Tubular steel frame with plastic plate and pluggable hook, for fastening or hanging the flood light. Practical, non-slip handle. On/Off switch.
- Modern, energy-saving LED area flood light with high light intensity. Brightness of the LEDs adjustable in 3 stages. Radiation angle of 120° for high illumination. Colour temperature 6,500 K. Efficient heat dissipation prevents overheating. For continuous operation.
- Power supply 220–240 V, 138 W, for mains operation included. Holder for ROLLER'S Li-Ion 21.6 V battery integrated into the housing for cordless instead of mains operation.
- **Li-Ion 22V Technology**
Highly resistant Li-Ion 21.6 V batteries with 2.5, 5.0 or 9.0 Ah capacity, for long life. Powerful and light. Li-Ion 21.6 V, 2.5 Ah for approx. 5.4 operating hours, 5.0 Ah for approx. 10.9 operating hours, 9.0 Ah for approx. 19.6 operating hours in brightness stage 1 with one battery charge*. Graduated charging status indicator with coloured LEDs. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. 100–240 V, 50–60 Hz, 90 W rapid charger or 100–240 V, 50–60 Hz, 290 W rapid charger, for shorter charging times (accessories).
- Practical, collapsible, telescopic tripod stand, for exact positioning of the LED flood light (accessory). Only 1.9 kg. Height-adjustable from 615 to 1590 mm from the floor.

Scope of Delivery

Art.-No.

kr

ROLLER'S *Worklight 2800 22V Set Power-Edition*

LED area flood light for construction sites; 3 brightness stages, tubular steel frame with plastic plate, pluggable hook, power supply 220–240 V, 138 W without battery, without charger

175210 A220

1 790,00

ROLLER'S *Worklight 2800 22V Set*

LED area flood light for construction sites; 3 brightness stages, tubular steel frame with plastic plate, pluggable hook, power supply 220–240 V, 138 W, Li-Ion 21.6 V, 2.5 Ah battery, 220–240 V, 70 W rapid charger

175211 A220

5 640,00

Accessories

Li-Ion 21,6 V, 2.5 Ah battery

571571 A22

3 200,00

Li-Ion 21,6 V, 5.0 Ah battery

571581 A22

3 840,00

Li-Ion 21,6 V, 9.0 Ah battery

571583 A22

5 120,00

100–240 V, 50–60 Hz, 90 W rapid charger

571585 A220

2 170,00

100–240 V, 50–60 Hz, 290 W rapid charger

571587 A220

5 120,00

ROLLER'S telescopic stand 3B

on tripod, height-adjustable, collapsible

175230 A

390,00

