

# ROLLER'S Centro

## S1 / SR / S2/3.5 / DP

Accessory for ROLLER'S Centro S1, Centro SR, Centro S3, Centro S2 / 3.5, Centro DP and other makes Art.-No. kr



<b>Drilling template drill stand T</b> for easy setting of the fastening holes	183605 R	720,00
<b>Laser drilling centre pointer</b>	183604 R	1 610,00
<b>Carbide masonry drills Ø 15 mm SDS-plus</b> for hammer anchors M12	079018	350,00
<b>Hammer anchor M12 (concrete), 50 pieces</b>	079005 R50	1 360,00
<b>Setting iron for hammer anchor M 12</b>	182050 R	200,00
<b>Carbide masonry drills Ø 20 mm SDS-plus</b> for splaying anchors M12	079019	790,00
<b>Splaying anchor M12, pack of 10, for masonry, reusable</b>	079006 R10	1 270,00
<b>Quick clamping set 160</b> for fastening the drilling stand with anchors, consisting of cord threaded bar 160 mm with M12 × 52 thread, quick clamping nut, washer.	079010	900,00
<b>Quick clamping set 500</b> for fastening the drilling stand without anchor, consisting of cord threaded bar 500 mm, 2 quick clamping nuts, 2 washers	183607 R	670,00
<b>Vacuum fastening drill stand T</b> , consisting of sealing ring and cover plate with hose connection	183603 R	1 230,00
<b>Vacuum pump</b> , for vacuum ≤ - 900 mbar (90%), consisting of dry running rotary slide pump, oil-free, performance 6 m <sup>3</sup> /h, condenser motor 230 V, 50–60 Hz, 250 W, splash water-protected, inside suction filter with silencer function and 5 m PVC fabric hose with bayonet coupling	183670 R220	23 600,00
<b>Start drilling aid G ½ UDKB</b> , with holes for extracting the drilling dust from the bore hole by a suction rotor for dust extraction (Art. No. 181160 R), with carbide masonry drill Ø 8 mm	180140 R	1 140,00
<b>Start drilling aid G ½ TDKB</b> , with holes for extracting the drilling dust from the bore hole, with carbide masonry drill Ø 8 mm	180145 R	1 140,00
<b>Carbide masonry drill Ø 8 mm</b> for drill aid	079013	240,00
<b>Pressurised water tank</b> for 10 l of water, for wet drilling without water connection	182006 A	2 540,00
<b>Water extractor</b> for wet drilling up to Ø 170 mm, consisting of water collection ring with sealing ring, rubber washer Ø 200 mm and universal pressure pad for all ROLLER'S drilling stands.	183606 R	4 870,00
<b>Rubber disc, Ø 200 mm</b> , pack of 10, for water extractor	183675 R10	930,00
<b>Suction rotor for sucking off dust</b> with G ½ male thread, UNC 1¼ male thread and with connection for ROLLER'S Protector 2 and other suitable extractors	180160 R	2 150,00
<b>Levelling block</b> magnetic, for aligning the drill stand	182010 A	930,00
<b>Drilling crown extension 200 mm</b>	180155 R	760,00
<b>Easy loosening ring</b> for easy loosening of the diamond core drilling crown	180015	260,00
<b>Sharpening stone</b> for diamond core drilling crowns	079012	800,00
<b>Single open ended wrench SW 41</b> for loosening of the drilling crown	079003	480,00
<b>ROLLER'S Protector 2 L / M</b> Dry and wet extractor, certified as extractor and dust extractor for extracting health hazardous dusts in accordance with EN 60335-2-69	See page 207	