

ROLLER'S Axial-Press H

Patent DE 10 2004 018 429
Patent ES 2 273 563
Patent FR 05 03513



For systems:
e. g. AC-FIX,
aquatherm,
BARBI,
Brass & Fittings,
COMAP,
EUROP'FLUIDES,
FERRO systems BRASELI,
Fittings Estándar,
PB TUB,
PLÁSTICOS FERRO,
REVI,
RIQUIER,
TECE,
TIEMME,
VELTA

German Top Quality



Handy, robust, universal manual axial press for compression sleeve connections Ø 12–22 mm (ROLLER'S Axial-Press HK), Ø 12–32 mm (ROLLER'S Axial-Press H).

- Compact design, comfortable weight, only 1.1 kg (ROLLER'S Axial-Press HK) or only 1.4 kg (ROLLER'S Axial-Press H). Can be used everywhere, even in confined spaces.
- Fast feed and fast return for fast work.
- Selectable compression head position (**Patent DE 10 2004 018 429, Patent ES 2 273 563, Patent FR 05 03513**) for pressing compression sleeve connectors with a clamping distance of up to 161 mm in one action and for double pressings. Stroke length 66 mm.
- ROLLER'S Axial-Press H with overload protection
- Full range of system-specific ROLLER'S compression heads for compression sleeve system, as well as ROLLER'S compression heads with spring catch for accommodating conventional pressing inserts, see page 132–133.
- **Double pressing heads**
ROLLER'S double pressing heads with two mountings that merge into each other, for pipe connectors of different dimensions, see page 132. No changing of pressing heads. Super fast and easy.
- Hybrid and manual pipe expander as well as full range of system-specific ROLLER'S expander heads P for all common compression sleeve systems, according to the requirements of the respective compression sleeve system, see page 134–137.

Scope of Delivery

Art.-No.

ROLLER'S Axial-Press HK drive unit	574302 A
ROLLER'S Axial-Press H drive unit	574300 AX

Accessories

ROLLER'S compression heads	See page 132–133
Carrying case for ROLLER'S Axial-Press HK/H drive unit and compression heads	574437 R
Case with inlay for drive unit ROLLER'S Axial-Press HK and compression heads	574352 A

ROLLER'S compression heads

Accessory for ROLLER'S Axial-Press H / HK, Axial-Press 25 22 V ACC / 25 L 22 V ACC

Choose your own compression heads!
System-specific compression heads for all common compression sleeve systems Ø 12–40 mm.

- **Full range of system-specific ROLLER'S compression heads** for all common compression sleeve systems, according to the requirements of the respective compression sleeve system as well as ROLLER'S compression heads with spring catch for accommodating conventional pressing inserts, see table page 133.
- For perfectly system-conformant pressing.
- Quickly and easily changeable, without tools.

ROLLER'S double pressing heads
with two mountings that merge into each other, for pipe connectors of different dimensions. No changing of pressing heads. Super fast and easy.

Double compression head RH 16/20, pack of 2
for 16 and 20 mm pipe connectors

ROLLER'S compression heads Basic with spring
for conventional pressing inserts

Basic 20, pack of 2
for pipe connectors 20 mm and for pressing inserts external-Ø 20 mm

Basic 25, pack of 2
for pipe connectors 25 mm and for pressing inserts external-Ø 25 mm

Basic 32, pack of 2
for pipe connectors 32 mm and for pressing inserts external-Ø 32 mm

ROLLER'S compression head UNI T/L
for T-pieces, brackets, distributors in combination with another compression head;
for adaptors, in combination with a resting bolt

Art.-No.

ROLLER'S resting bolt
for adaptors, in combination with ROLLER'S compression head UNI T/L

Resting bolt 5/8"	573647 R
Resting bolt 1/2"	573648 R
Resting bolt 3/4"	573649 R

