ROLLER'S Corso W INOX

10-32/40 S





Compact, robust, quality pipe cutter with needle-bearing-mounted cutting wheel and counterpressure rollers, especially for corrugated metal hoses (corrugated pipes) made of stainless steel, also jacketed, DN 10-32 (40), \emptyset $\frac{3}{2}$ -1½" (2").

- For fast, easy, precise and right-angled cutting.
- Sturdy telescopic single, long spindle guide, needle-bearing-mounted cutting
 wheel and 2 needle-bearing-mounted counterpressure rollers. 3 additional guide
 rollers each on both sides, arranged triangularly, for optimum straight guidance
 of the corrugated pipe.
- Ergonomic, handy rotary handle enables powerful engagement of the spindle.
- Proven quality cutting wheel made from tenacious special steel for extremely long life.

 Designation
 Art.-No.

 ROLLER'S Corso W INOX 10-32/40 S
 113450 A

Accessories

ROLLER'S cutting wheel W INOX 10-32/40 S on needle bearing

113461 A

ROLLER'S Corso Cu



With telescopic spindle



With quick adjustment



German Top Quality





Compact, robust quality tube cutter for copper tubes and others, \emptyset 3-64 mm, \emptyset ½-2½", wall thickness s \leq 3 mm.

- Handy, ergonomic rotary handle of metal enables powerful engagement of the spindle.
- Precision, wide cutting wheel bearing on hardened, twist-protected axle ensures right-angled cutting.
- Proven quality cutting wheel made of tenacious special steel for extremely long life. Only one cutting wheel for the entire working range Ø 3-64 mm, to fit all ROLLER'S Corso Cu pipe cutters.
- Cutting wheel protected against touching the guide rollers by in-feed limitation.
- ROLLER'S Corso Cu 3–35

With space-saving, special smooth action telescopic spindle for fast, easy engagement and simple, right-angled cutting. Quick cutting wheel change without tools. Integrate pipe deburrer with specially ground, exchangeable deburring blade. 4 hardened counter pressure rollers, for exact guiding and long life.

ROLLER'S Corso Cu 8-42, Cu 8-64

Fast positioning of the cutting wheel in both directions. No unnecessary forward and backward turning of the spindle. For fast working. Strong spindle, long spindle guide and hardened guide rollers, for exact guiding on the pipe and long life.

Designation	Pipes Ø	ArtNo.	
ROLLER'S Cors	o Cu		
Cu 3-35	3-35 mm / 1/8-1 3/8"	113340 A	
Cu 8-42	8-42 mm / 1 ³ / ₈ -1 3/4"	113370 A	
Cu 8-64	8-64 mm / 1/8-21/2"	113410 A	
Accessories			
ROLLER'S cutting will (wall thickness $s \le 3$ m	heel Cu 3–120, s 3 nm) for ROLLER'S Corso Cu	113225 A	
Universal deburring blade specially ground		113360	