ROLLER'S Scirocco 50

High-performance, highly efficient, electric dehumidifier/building dryer for commercial use in trade and industry. Dehumidification capacity of ≤ 50 l/24 h, air volume ≤ 265 m³/h.

- *For drying rooms quickly and effectively, e.g. after water damage and floods – for drying basements and other rooms and accelerated drying of concrete, masonry, plaster, screed, etc.*
- *Compact, handy design in sturdy plastic case. Weight 21 kg*
- *Large air intake surface area with washable air filters. Top air outlet for optimum air circulation.*
- *Condensation discharge into an internal 7.7 l condensation tank, hose can be fed out at the rear, for discharging condensation into a tank to be provided or directly into a drain pipe.*
- ***Electronic hygrostat***
  for controlling the desired air humidity: Automatic switching off when target humidity has been reached – automatic restarting with increasing humidity.
- ***Cooling unit***
  High dehumidification performance by the high-quality cooling unit with highly efficient rotary compressor and high-performance capacitor motor 230 V, 680 W, with electronic thawing, for continuous operation. Very quiet running, also suitable for occupied rooms. Dehumidification capacity of ≤ 50 l/24 h, air volume ≤ 265 m³/h. High quality refrigerant R-290.
- ***Electronic control unit***
  Large illuminated control panel, with clear display of actual and nominal humidity, operating state of the cooling unit, thawing function. Buttons for setting the desired humidity to between 30% and 90% in 5 % increments, as well as setting for continuous operation. Buttons for 2 fan speeds. Button for timer. Memory function saves the settings for automatic continuation of operation following a power failure.
- *Automatic switching off by switch-off signal when using the internal 7.7 l condensation tank when the maximum condensation level is reached*
- *Sturdy plastic housing with running rollers for easy transport.*
- *Operating hours counter and power consumption meter, e.g. for reporting to claims adjusters/customers (accessory).*
- *Condensation tank with condensation pump for feeding the condensation out of the condensation tank to a higher container or into a wash basin (accessory).*
- *ROLLER'S Mistral electric construction ventilator for supporting ROLLER'S Scirocco 50 / 80 (accessory). For improved air exchange and for faster drying after floods and mains water damage, see page 202.*

Scope of Delivery	*Art.-No.*
ROLLER'S Scirocco 50 Set	
Electric dehumidifier/building drier with internal 7.7 l condensation tank. In sturdy plastic case with running rollers	*132011 A220*
Accessories	
Condensation tank with pump Scirocco 50 *For feeding the condensation out of the condensation tank to a higher container or into a wash basin. Transport height ≤ 2 m*	*132129 A220*
Operating hours counter and power consumption meter *e.g. for reporting to claims adjusters/ customers.*	*132132 A220*
ROLLER'S Control W *electric moisture measuring device for measuring the moisture in building materials, e.g. concrete, masonry, plaster, wood. In a bag.*	*132115 A*
ROLLER'S Mistral 1360 / 2050 *electric construction ventilator*	*see page 202*